

Microcom 520

Thermal Desktop Printer

**Ticket, Label, Receipt &
Wristband Thermal Printer**



**Easy to learn.
Easy to operate.
Easy on the budget.**

Direct thermal printer

203 dpi print resolution

6" per second print speed

2.2" print width

Stock up to 7 mils thick

5" OD internal supply holder

Multiple built-in sensors

Serial, USB, Ethernet or WiFi

Label Peel and Dispense option

Weight: 2.4 lbs.

Memory: 8MB SDRAM (standard)

4MB FLASH

Drivers: Win. 7, 8, 8.1, 10, Linux

Emulation: ZPL

FCC, UL, CE certified

Microcom Model 520

Microcom's model 520 provides an efficient, affordable printing solution for Windows, Linux, and ZPL applications. Its design offers internal storage for continuous, die-cut, and black sense mark media (up to 5" OD roll) as well as rear-loading for fanfold labels and event tickets. Model 520's small foot print combined with the reliability customers expect from Microcom products make it the ideal choice for two inch wide printing applications.

Optional Features Available

In addition to the many standard features on this model, the 520 is also available with multiple connectivity options, LCD display screen, and a peel and dispense feature for label printing.

Application Overview:

- Event Ticketing
- Security
- Wristbands
- Inventory/Warehousing
- Retail
- Healthcare/Pharmaceutical



(740) 548-6262

8220 Green Meadows Drive North

Lewis Center, Ohio 43035

www.microcomcorp.com



Microcom 520 Thermal Desktop Printer

For more information please our website at www.microcomcorp.com or call (740) 548-6262

Performance Summary ♦♦♦

- Direct thermal, on-demand printing
- 203 dpi resolution
- 2.2" (56 mm) maximum print width – 2.4" (62 mm) maximum paper width
- Up to 6" (152 mm) per second print speed
- Print length: 0.4" (10 mm) minimum – 90" (2300 mm) maximum
- Sensors: top cover position, TPH overheating protection, black line sensor, paper exit sensor
- LCD screen and peel and dispense features optional
- Microsoft Windows® 7, 8, 8.1, 10, and Linux
- ZPL emulation
- Self-centering media guides
- Media spindle can hold .05" or 1" paper roll core
- Lift up print head for easy cleaning and replacement
- Rated for 100% duty cycle usage for printing of large batches of tickets

Bar Codes ♦♦♦

- Code 39
- ITF25
- Code 128
- Code 93
- HBIC
- UPC-A
- UPC-E
- EAN-8
- EAN-13
- EAN-UCC
- Postnet
- Codabar
- UPC2
- UPC5

2D Symbolologies — PDF-417 — Maxicode — QR — Matrix25

Memory ♦♦♦

- SDRAM: 8MB
- FLASH: 4MB, can be upgraded to 8MB

Communication Interfaces ♦♦♦

—Serial, USB, Ethernet or WiFi: Specify at time of order

Physical Dimensions ♦♦♦

Height	Width	Depth	Weight
6.7" (171 mm)	4.4" (111 mm)	8.7" (221 mm)	2.4 lbs. (1.1 kg)

Environmental Conditions ♦♦♦

- Storage conditions: -40° F to 140° F (-40° C to 60° C)
- Operation temperature: 40° F to 104° F (5° C to 40° C)
- Output: 24V DC, 1.5A
- Input: 100 VAC – 240 VAC, 1.5 AMPS

Compliance ♦♦♦

- FCC
- UL
- CE

Warranty ♦♦♦

- One year limited warranty



(740) 548-6262
8220 Green Meadows Drive North
Lewis Center, Ohio 43035

Visit us at www.microcomcorp.com

References in this publication to Microcom Corporation products or services do not imply that we intend to make them available in all countries.

© Copyright 2018 Microcom Corporation. All rights reserved.
Microcom Corporation reserves the right to make improvements to their products at any time without prior notice. The information contained herein is subject to change without notice. Microcom Corporation shall not be liable for technical or editorial omissions contained herein. Reproduction, adaptation or translation without prior written permission is prohibited, except as allowed under the copyright laws. All company and product names are trademarks or registered trademarks of their respective owner.